

# HDL-PC & HDL-R

Maximise drip system longevity with robust material construction and pressure compensation for standard and reclaimed applications.

## KEY BENEFITS

- Pressure-compensating emitters for consistent flow and uniform coverage
- Colour-coded stripes provide easy identification of flow
- UV resistance facilitates product longevity
- Stretch-wrapped coils stay intact and make installation quick and easy
- Superior grit tolerance provided by proprietary emitter design with multiple inlet filters, a wide turbulent labyrinth, and a full-size outlet pool
- Reclaimed product (HDL-R) identified by purple stripes assists in visual identification when using non-potable water

## PRODUCT SPECIFICATIONS

- Available flow rates: 2.1, 3.4 l/hr
- Available emitter spacing: 30 cm, 45 cm, 60 cm
- Tubing dimensions: 16.76 mm x 14.22 mm (outside/inside diameter)
- Available without emitter (HDL-BLNK)

## OPERATING SPECIFICATIONS

- Operating range: 1 to 4.2 bar; 100 to 420 kPa
- Minimum filtration: 120 mesh (125 microns)
- Warranty period: 5 years



HDL-PC



HDL-R (Reclaimed)

Optional colour for reclaimed water sources, available for 17 mm only.



## HUNTER DRIPLINE COLOUR CODE

### STRIPE COLOUR

- 3.4 l/hr - Black
- 2.1 l/hr GPH - Grey
- Reclaimed - Purple

### TUBING COLOUR

- HDL-PC - Light brown tubing, pressure-compensating
- HDL-R - Light brown with purple stripe, pressure-compensating, reclaimed

## HDL - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Spacing	3 Length	4 Options
HDL-06 = 2.1l/hr flow	12 = 30 cm	250 = 75 m	PC = Pressure-compensating
HDL-09 = 3.4l/hr flow	18 = 45 cm	500 = 150 m	R = Reclaimed (available in 2.1 and 3.4 l/hr models only)
	24 = 60 cm	1K = 300 m	

### Example:

HDL-09-12-1K-PC = 3.4 l/hr, 30 cm emitter spacing, 300 m coil with PC emitter

Note: Two HDL-PC products are available in 30 m coils: HDL-06-12-100-PC and HDL-09-12-100-PC

## MAXIMUM RUN LENGTHS

HDL-PC/HDL-R - 1.5 l/hr				HDL-PC/HDL-R - 2.1 l/hr				HDL-PC/HDL-R - 3.4 l/hr			
Pressure (bar; kPa)	Emitter Spacing (cm)			Pressure (bar; kPa)	Emitter Spacing (cm)			Pressure (bar; kPa)	Emitter Spacing (cm)		
	30	45	60		30	45	60		30	45	60
1.0; 100	87	123	156	1.0; 100	72	101	129	1.0; 100	50	71	89
2.0; 200	125	177	224	2.0; 200	103	147	186	2.0; 200	72	101	128
3.0; 300	149	210	266	3.0; 300	123	174	220	3.0; 300	85	120	153
4.0; 400	167	235	299	4.0; 400	137	194	247	4.0; 400	96	134	171