

ICC2

This reliable control system can run conventional, two-wire, or hybrid operations with the option to upgrade to Centralus™ cloud-based control.

KEY BENEFITS

- Number of stations:
 - Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestal)
 - With two-wire EZDS: up to 54 (all enclosure options)
- 4 independent irrigation programs (8 start times each) allow for customised scheduling
- 12-hour maximum station run time provides flexibility for low-flow zones
- Any 2 programs can operate simultaneously, providing more efficient watering
- 1 sensor input available for use with Solar Sync™ or any Klik sensors
- 1 P/MV output for pump start relay and master valve activation
- Backward compatibility to original ICC controllers allows for quick updates to older systems
- Upgradeable to Centralus software for web-based central control options

OPERATING SPECIFICATIONS

- Transformer input: 120/230 VAC
- Transformer output (24 VAC): 1.4 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.56 A
- Approvals: Wall Mounts IP44, Plastic Pedestal IP34, NEMA 3R, UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- WIFIKIT or LANKIT communications for Centralus web-based control
- Compatible with Flow-Klik™ sensor for catastrophic high-flow shutdown

ICC2	
Model	Description
I2C-800-PL	8-station base model, plastic outdoor wall mount
I2C-800-M	8-station base model, grey metal outdoor, wall mount
I2C-800-SS	8-station base model, stainless steel, wall mount
I2C-800-PP	8-station base model, plastic pedestal
ICC-FPUP2	ICC2 retrofit kit for original ICC controllers
ICC-PED	Grey pedestal for metal wall mount
ICC-PED-SS	Stainless steel pedestal for stainless wall mount
ICC-PWB	Optional pedestal wiring board for metal pedestals

ICC2 SERIES STATION EXPANSION	
Model	Description
ICM-400	4-station plug-in module with enhanced surge suppression
ICM-800	8-station plug-in module with enhanced surge suppression
ICM-2200	22-station expansion module (one per controller)
EZ-DM	54-station decoder output module (one per controller)
EZ-1	Single-station EZ decoder



Plastic

Height: 30.5 cm
Width: 35 cm
Depth: 12.7 cm

Metal

(grey or stainless steel)
Height: 40.6 cm
Width: 33 cm
Depth: 12.7 cm



Metal Pedestal

(grey or stainless steel)
Height: 91.4 cm
Width: 29.2 cm
Depth: 12.7 cm

Plastic Pedestal

Height: 99 cm
Width: 61 cm
Depth: 43 cm


Compatible with:



**Solar Sync
Sensor**
Page 146



ROAM Remote
Page 137
ROAM XL Remote
Page 138



**EZ Decoder
System**
Page 134



Smart WaterMark

Recognised as a responsible water-saving tool when used with a Solar Sync sensor