

SPRAY ACCESSORIES

Spray accessories provide flexibility for installation and maintenance of spray systems.

SJ SWING JOINTS

Features

- Unique swivel ells on both ends for easy installation in any configuration.
- Swing joints are built with air-tight connection points for long-term reliability. Pressure loss charts for SJ products on **page 254**

Models

- SJ-506: ½" threaded x 15 cm length
- SJ-512: ½" threaded x 30 cm length
- SJ-7506: ½" x ¾" threaded x 15 cm length
- SJ-7512: ½" x ¾" threaded x 30 cm length
- SJ-706: ¾" threaded x 15 cm length
- SJ-712: ¾" threaded x 30 cm length

Operating Specifications

- Pressure-rated to 10 bar; 1000 kPa
- Warranty period: 2 years



SJ Swing Joint
15 cm or 30 cm links

HUNTER SPIRAL BARB ELBOWS

Features

- Compatible with Flex_{SG} and other brands for a customised swing joint
- Acetal material for sharp barbs

Models

- HSBE-050: ½" male x spiral barb elbow
- HSBE-075: ¾" male x spiral barb elbow
- HSBE TOOL: Insert tool

Operating Specifications

- Operating pressure: Up to 5.5 bar; 550 kPa
- Warranty period: 2 years



Spiral Barb Elbows
HSBE-TOOL, HSBE-050, HSBE-075

FLEX_{SG} TUBING

Features

- Engineered to resist kinking
- Textured for easy grip
- Linear low-density polyethylene material
- Meets ASTM D2104, D2239, D2737

Models

- FLEXSG: 30 m roll
- FLEXSG-18: 45 cm pre-cut lengths

Operating Specifications

- Operating pressure: up to 5.5 bar; 550 kPa
- Warranty period: 2 years



FLEX_{SG} Tubing
30 m and 45 cm pre-cut lengths
Inside diameter: 1.2 cm

PRO-SPRAY SHUTOFF CAP

Features

- Caps off the Pro-Spray for maintenance or drip conversions
- Maintains a clean look to the landscape

Models

- 213600SP

SHUTOFF NOZZLE

Features

- Easy shutoff for spray systems
- Allows heads to pop-up for easy visibility
- Use with Pro-Spray and PS Ultra models

Models

- 916400SP



Pro-Spray Shutoff Cap
P/N 213600SP



Shutoff Nozzle
P/N 916400SP