

TECHNICAL DATA SHEET

ELBEblue line STG 200

**Flexible sheets for waterproofing made of plasticised polyvinyl chloride (PVC-P)
fibre-reinforced, slip protected; as lining material for swimming pools**

produced according EN 13967

Damp proof sheet Type A and Tanking sheet Type T



07 1213-CPD-036

Technical Data

Thickness	[mm]	1,40	± 10 %	EN 1849-2
Width	[cm]	165	± 5 mm	
Colour				
Embossing		pyramids		
Maximum tensile force	[N/50mm]	long./transv.: ≥ 1100	EN 12311-2	
Elongation at break	[%]	long./transv.: ≥ 18	EN 12311-2	
Tear resistance	[N]	long./transv.: ≥ 400	EN 12310-1	
Dimensional stability (80°C 6 h)	[%]	long./transv.: ≤ 2,0	EN 1107-2	
Straightness (g)	[mm]	g ≤ 50	EN 1848-2	
Flatness (p)	[mm]	p ≤ 10	EN 1848-2	
Water tightness (400 kPa, 72 h)		tight	EN 1928 B	
Durability against aging		tight at 60 kPa	EN 1296	
Durability against chemicals (sat. basic sol.)		tight at 60 kPa	EN 1847	
Reaction to fire		class E	EN 13501-1	
Resistance to impact (height = 300mm)		tight	EN 12691 A	
Resistance to static load (20 kg/24 h)		passed	EN 12730 B	
Joint shear resistance	[N/50mm]	long./transv.: ≥ 1100	EN 12317-2	
Foldability at low temperature (- 35°C)		passed	EN 495-5	

Properties

slip resistant surface by embossing (best class C to EN 13451)
stabilized against UV-rays
cold resistant and resistant to weathering
good weldability
free of heavy metals and physiological unobjectionable according to EN 71/3
antimicrobially equipped
resistant to all usual chemicals for water treatment in swimming pools (according to the chemical instructions), at water temperature max. 30 degrees
not resistant to tar, bitumen, oil, fuel and other solvents
not resistant in direct contact to other plastics, f.e. polystyrene

Storage and Processing

Rolls horizontal on pallet, protected against sun, rain and other weather influences, at temperature between 5 and 25 degrees C.
Processing shall be at temperature min. 10 degrees C.

Legal notice

The customer/installer has to check the applicability of the product for the intended use. He is responsible for the proper application, usage and processing of the product.

We assure the correct quality of our products according to our conditions of sale and delivery. All declarations comply with our recent knowledge.

In behalf of the warranty the distributor has to secure, that his customers are informed about our installation-, care- and cleaning-instructions.

